

Tileguard[®] Colour

High gloss 100% acrylic water based top coat designed to beautify most types of roofing surface.

Application:

Recommended for airless spraying on to most roofing surfaces which have been previously primed or sealed.

Not recommended for Terracotta tiles.

Should be applied 2 coats for maximum gloss and durability.

Not recommended for application below 14°C or over 32°C air temperature.

This is particularly important when coating metal roofs.

As a general rule: **“If the roof is too hot to touch, it is too hot to paint”**.

Adhesion:

Excellent adhesion to most primed or sealed roofing surfaces.

Coverage:

Cement tiles: 90 sq. mt. / 20 lt. Metal and non-porous tiles: 120 sq. mt. / 20 lt.

This may vary slightly depending on application conditions and the surface to be sealed.

Safety:

Tileguard[®] colour dry film is non-hazardous and suitable for roofs used to collect drinking water.

When coating roofs used to collect drinking water, disconnect down pipes for two good rainfalls, then reconnect.

If contact with eyes or skin occurs, wash thoroughly with water.

If accidentally swallowed, drink plenty of milk or water.

Important Note:

We can only guarantee the quality of our products to the point of despatch as the use of our products is beyond our control.

Disclaimer:

The information in this data sheet is based on data obtained from our suppliers which we believe to be reliable. It is intended as a fair description of our products. We offer the data in good faith but cannot guarantee the accuracy of the information obtained from our suppliers as it is beyond our control.