

Tileguard® HIGH BUILD SEALER

High solids 100% acrylic water based coating designed to seal aged, pitted cement roof tiles prior to top coating.

Application:

Recommended for airless spraying on to very porous aged, pitted cement roof tiles to seal and level the damaged surface prior to top coating.

Not recommended for Terracotta tiles.

Not recommended for application below 14 °C or over 32°C air temperature.

As a general rule: **“If the roof is too hot to touch, it is too hot to paint”**.

Adhesion:

Excellent adhesion to primed or highly porous cement tiles.

If the tile surface is chalky or powdery, apply **Tileguard® Primer** first.

Coverage:

About 70 sq. mt. / 20 lt. This may vary slightly depending on application conditions and the surface porosity.

Safety:

Tileguard® HIGH BUILD SEALER dry film is non- hazardous and suitable for roofs used to collect drinking water.

When coating roofs used to collect drinking water, disconnect down pipes for two good rainfalls then reconnect.

If contact with eyes or skin occurs, wash thoroughly with water.

If accidentally swallowed, drink plenty of milk or water.

Important Note:

We can only guarantee the quality of our products to the point of despatch as the use of our products is beyond our control.

Disclaimer:

The information in this data sheet is based on data obtained from our suppliers which we believe to be reliable. It is intended as a fair description of our products. We offer the data in good faith but cannot guarantee the accuracy of the information obtained from our suppliers as it is beyond our control.