

Tileguard[®] Primer

A water based acrylic co-polymer coating designed to penetrate and bind oxidised cement roof tile surfaces prior to top coating. Also suitable as a key coat for most rust-free metal roof surfaces.

Application:

When airless spraying **Tileguard[®] Primer** over cement roof tiles, allow 2 hours before applying next coat. Allow 24 hours when used over metal surfaces and some non-porous cement tiles to maximize adhesion.

Not recommended for Terracotta tiles.

Not recommended for application below 14°C or over 32°C air temperature.

When airless spraying over metal, do not let the surface temperature exceed 45°C to prevent the primer from cooking.

As a general rule for all surfaces, **“If the roof is too hot to touch, it is too hot to paint”**.

Coverage:

Cement tiles: 110 sq. mt. /20 lt. Metal and non-porous tiles: 120-140 sq. mt. / 20 lt.

This may vary slightly depending on application conditions and the surface to be primed.

Safety:

Tileguard[®] Primer dry film is non-hazardous and suitable for roofs used to collect drinking water.

When coating roofs used to collect drinking water, disconnect down pipes for two good rainfalls then reconnect.

If contact with eyes or skin occurs, wash thoroughly with water.

If accidentally swallowed, drink plenty of milk or water.

Important Note:

We can only guarantee the quality of our products to the point of despatch as the use of our products is beyond our control.

Disclaimer:

The information in this data sheet is based on data obtained from our suppliers which we believe to be reliable. It is intended as a fair description of our products. We offer the data in good faith but cannot guarantee the accuracy of the information obtained from our suppliers as it is beyond our control.