

Tileguard[®] SEALER

100% acrylic water based coating designed to seal medium porous cement roof tiles.

Application:

Recommended for airless spraying on to cement roof tiles which have been previously primed, or medium porous tiles where a primer is not required.

Not recommended for Terracotta tiles.

Not recommended for application below 14°C or above 32°C air temperature.

As a general rule: **If the roof is too hot to touch, it is too hot to paint”.**

Adhesion:

Excellent adhesion to primed or medium porous tiles.

If the tile surface is chalky or powdery, apply **Tileguard[®] PRIMER** first.

Coverage:

About 80 sq. mt. / 20 lt. This may vary slightly depending on application conditions and the surface to be sealed.

Safety:

Tileguard[®] SEALER dry film is non-hazardous and suitable for roofs used to collect drinking water.

When coating roofs used to collect drinking water, disconnect down pipes for two good rainfalls then reconnect.

If contact with eyes or skin occurs, wash thoroughly with water.

If accidentally swallowed, drink plenty of milk or water.

Important Note:

We can only guarantee the quality of our products to the point of despatch as the use of our products is beyond our control.

Disclaimer:

The information in this data sheet is based on data obtained from our suppliers which we believe to be reliable. It is intended as a fair description of our products. We offer the data in good faith but cannot guarantee the accuracy of the information obtained from our suppliers as it is beyond our control.